

SMOKE DETECTOR TESTOR

CATALOGUE Model. **FPE.25S**

CERTIFICATE ISO 9001:2000/CE/CNS12681

FOR USE

ALL FIRE ALARM SYSTEMS UL/NFPA



DUCUMENTATION

DATASHEET

- At last there's an alternative to blow adyers, heat guns and other inappropriate appliances in the testing of heat detectors. You don't need to weigh yourself down with electrical heat appliances, cords and ladders, because **Heat Detector Tester** puts every detector within easy reach. **Heat Detector Tester** is from Home safeguard Industries, so it has our commitment of quality and convenience. With **Heat Detector Tester** you'll run through your entire network in minutes, not hours. And you won't have to worry about high-mounted units. They're taken care of with **Heat Detector Tester**.

- **An instant heat source that's safe and nontoxic.**

Heat Detector Tester is a real breakthrough. **The secret:** our exclusive Heat Pack, an environmentally safe, disposable product that heats to 140 - 150 F within minutes. Simply remove a packet from the Heat Pack and place it in the adjustable cup. A specially designed plastic retainer ring holds the packet securely for up to 30 minutes of uninterrupted testing. Then, once the Heat Pack has cooled, replace it with another and continue. Used packs are completely nontoxic, so they're disposable in any household or commercial container.

- **Quick, reliable and economical.**

Every makeshift test method has its own weaknesses. With a heat gun or blow dryer, for example, you can't be sure you're applying the right amount of heat for the right amount of time. Combine that with a fully extended ladder and power cord, and you've got a recipe for trouble.

- **Heat Detector Tester** is different. It was designed with one purpose in mind: to provide quick, reliable testing with a maximum of safety, regardless of the number of units to be tested. What's more, with a **Heat Detector Tester** you can be sure your system is tested properly and on schedule a real benefit, in terms of costs and peace of mind.

- **Heat Detector Tester** is complete and ready for use. Each Kit contains an adjustable cup for testing of wall-or ceiling-mounted units, a retainer ring, Heat Packs and extension tubes. **Heat Detector Tester** was designed to allow the testing of rate-of-rise and rate-compensation detectors in the 135 F range. For more information about features and pricing, see your Home Safeguard Industries product distributor.

INSTRUCTIONS FOR USE

- This product is UL Listed for testing a smoke detector's function per NFPA 72 and for use with smoke alarms listed to UL standards 217 and 268 when used as follows:
 - From a distance of 2 to 4 ft. (.0 -12m) aim spray for 1-2 seconds at the vents or side of the detector. When using this product in an enclosed dispenser device only a 1/2-1 second spray is typically required to activate the alarm.
 - Alarm will sound within 1-10 seconds if the detector functions properly unless the detector has a built-in delay circuit. Detectors with delay circuits should be sprayed 1 or 2 additional times to activate the alarm.
 - When activated, detector should alarm for 10 to 15 seconds.Note: Excessive spraying may affect the detector's sensitivity.